


# SLE

SLE applications	81
SLE dimensions	82
SLE types	84
SLE sizes	86
SLE parts	87
SLE assembly	88
SLE connectors	83
SLE part numbers	92
SLE accessories	98



closed + open


## SLE CHARACTERISTICS

The SLE is available as **SLA** with aluminium T- or slot-profile, as **SLE** with plastic inserts or plastic slot profile, as **SLS** with foam slot profile, as **SLP** with plastic divider PZ or as **SLR** with pipe or roll stays.



In steel, stainless steel and hardened material is the steel chain in case of large free carrying lengths, large quantities of cables and heavy-duty hydraulic hoses first choice.

- stay distributions in many variants
- stay fast assembly and disassembly
- simple shortening and lengthening
- shroud protecting pivot mechanics



### Travel

The maximum travel distance is determined by the arrangement and the additional weight (line weight). At normal arrangement the maximum travel is twice the free carrying length. Support rollers or similar constructive steps can increase this value. In gliding arrangement travel distances up to 100 meters are possible (application dependent). Exceeding this value additional constructive action is needed (see design guidelines).

### Travel speed

The standard and the stainless steel design is limited at 1m/s. Exceeding this and high dynamic loads caused by e.g. vibrations or high number of cycles require the use of the hardened (carbured) material.

### Acceleration


The acceleration in principle is not limited. Limits are achieved, by very long chains and line weight that cause extrem tensile forces.




### Temperature



The long term operating temperature is -20 °C to 600 °C (-40 °C stainless steel to 600 °C).

### Special types

- Stainless Steel
- Carburated (hardened)







the usable interior width is stay length - 2(e-f)

SLE	pitch	a	c	e	f	g	h	k	l <sup>1)</sup>	m	o	p	t	weight [kg/m]
120, 121, - , 128	50	20	35	10	6	7,5	7	1	9	7	12	20	4	2,3
220, 221, 225, 228	75	31	50	14	8	12	9	1,5	13	9	12	30	4	4,3 ( 5,8)
320, 321, 325, 328	100	49	75	16	10	17	11	2	18	12	12	50	4	7,9 ( 9,6)
520, 521, 525, 528	125	68	100	22	14	22	13	3	20	15	12	70	4	15,1 (16,9)
620, 621, 625, 628	175	118	150	22	14	26	13	3	20	15	24	115	8	19,3 (20,9)

the weight is given for the standard type with with a stay length of 100, values in brackets for closed version  
1) stay length + 2l is the width of the chain with sliders

bending radius R [mm]

120, 121, - , 128			60	100	150		250							
220, 221, 225, 228				100	150	200	250	300						
320, 321, 325, 328 <sup>1)</sup>					150	200	250	300	400					
520, 521, 525, 528 <sup>1)</sup>						200	250	300	400	500				
620, 621, 625 <sup>2)</sup> 628 <sup>1)</sup>							250	300	400	500	600			

<sup>1)</sup> SLE 328 from R200, SLE 528 from R300, SLE 628 from R400    <sup>2)</sup> SLE 625 from R300

the stay lengths are offered in steps of 1 mm


stay length    SLE plastic inserts Ø [mm]

120, 121, - , 128	40 ... 800													
220, 221, 225, 228	50 ... 900	10	15	20	25	30								
320, 321, 325, 328	60 ... 1000	10	15	20	25	30	35	40	45	50				
520, 521, 525, 528	70 ... 1200	10	15	20	25	30	35	40	45	50	55	60	65	70
620, 621, 625, 628	100 ..1200													

order example:


travel distance 3 m, bending radius 200 mm,  
cables: 1x15 mm, 8x8 mm, 3x12 mm, 2x22 mm,

normal arrangement




SLE 220 / 200    x    2325    / 200    /D/E    / 5 PZ 1 PT55  
type    / radius    x    length    / stay length    / connectors    / arrangement / stay distribution

Normal connector in outer radius




connector **E** in inner radius




SLE	connector screws
120	M 6
220	M 8
320	M10
520	M12
620	M12


connector **A**



connector **B**



connector **C** in outer radius



connector **D** in inner radius



## SLE TYPES

### SLE 120, 220, 320, 520, 620

The standard type is build with stays in every second chain link. The steel link energy chains can be opened in the inner and in the outer bending radius.




order example

<b>SLE 120</b>	/ 100	x 2050	/ 100	/ D	/ E	/ h	/ 2PZ
type	radius	length	stayw.	connect.	arran.	stay dist.	

### SLE 121, 221, 321, 521, 621

These designs are made with stays in each link. This increases the lateral stability and improves the guiding particularly of smaller diameter lines.



order example

<b>SLE 321</b>	/ 100	x 3100	/ 200	/ N	/ N	/ n	/ 5PZ, 3PT
type	radius	length	stayw.	connect.	arran.	stay dist.	

### SLE 225, 325, 525, 625

The closed types offer optimum protection of the lines against dust and cuts or other enviromental influences. At higher temperatures the covers **Silver Star** provide excellent protection.

The closed types also may be build out of the standard version.




order example

<b>SLE 225</b>	/ 200	x 2550	/ 150	/ N	/ N
type	radius	length	stayw.	connectors	

### SLE 128, 228, 328, 528, 628

These types are suitable for long travel, with slides on the upper strand or on the lower strand. For greater stability these energy chains are build with stays in each link. The energy chains are fitted with sliders, which have a very low coefficient of friction ( $\mu = 0.2$  to  $0.25$ ).

After reaching the wear limit the slider can be renewed and the energy chain will continue.



order example

<b>SLE 328</b>	/ 200	x 45000	/ 250	/ N	/ N	/ g	/ 3PZ
type	radius	length	stayw.	connect.	arran.	stay dist.	

Compared to standard chains the SLE series is characterized by the fact that the sturdy aluminium profile can be steplessly adapted to the requirements. Stay lengths of up to 1500 mm can be provided. The subdivision of the interior satisfies every requirement and guarantees optimized cable protection, even at very high accelerations and travel speeds.

The **SLA** (SLE with aluminum T-profile or aluminium slot-profile) is a highly customized and robust energy chain, which is chosen primarily for larger dimensions. The stays are milled in accordance with the requirements of the user with individual hole patterns.


For extreme applications, the variants SLA, SLS and SLE should be preferred, since these offer optimize cable guiding. In the case of high speed and acceleration a multi-layer arrangement of the cable should be avoided.

The **SLE** (SLE with plastic inserts or plastic slot-profile) ensures at high speeds a perfect guide and almost excludes errors during installation of the lines as even with this variation the hole pattern of the stays can be adjusted accurately to the needs of the lines. Plastic inserts are available in a 5 mm grid. The plastic slot-profile can be accurately ordered.

For limited installation space, the **SLS** (SLE with foam slot-profile) are used. Again, the optimal guiding of the lines at high speeds and acceleration is ensured. Well-known automotive manufacturers have used this type for years with the best experiences. All lines lie in the neutral axes of the energy chain.

For space reasons, the **SLP** (SLE with plastic divider PZ and others) can be selected. This inexpensive design allows the guiding of large amounts of cable. The highly variable distribution possibility through small steps of (3mm) in height, plus the Telescopic divider (PT) allows maximum space for all needs, even when changes take place.

The **SLR** (SLE with a pipe or roll stays) is manufactured only upon request. The pipe stay allows special material combinations, such as the exclusion of aluminum or the use of stainless steel and brass. The roll bar has advantages particularly for heavy lines with high friction and wear in terms of durability of the cables and hoses: Relative movements on the energy chain are compensated by the rolling motion of the stays.



## SLE SIZES




### SLE 120

standard type			
height:	35	width:	52 ... 812
inner height:	20	inner width:	40 ... 800




### SLE 220

standard type			
height:	50	width:	66 ... 916
inner height:	31	inner width:	50 ... 900



### SLE 320

standard type			
height:	75	width:	80 ... 1020
inner height:	49	inner width:	60 ... 1000



### SLE 520

standard type			
height:	100	width:	98 ... 1028
inner height:	68	inner width:	70 ... 1500




### SLE 620

standard type			
height:	150	width:	128 ... 1228
inner height:	118	inner width:	100 ... 1500

item name

- 1 link
- 2 connector link single
- 3 connector link double
- 4 connector angle
- 5 flange bolt
- 6 radius bolt
- 7 cover plate
- 8 retaining ring
- 9 aluminum C-profile
- 10 serrated screw
- 11 plastic (vertical) divider
- 12 outer cover
- 13 spacer
- 14 inner cover
- 15 band holder
- 16 band (steel / stainless steel)
- 17 threaded bolt
- 18 lock washer
- 19 locknut



The use of steel chains with steel bands (16) is limited to energy chains with a maximum length of 6 m. For reasons of rigidity longer energy chains have to be build by using the **silver star** covers.

## Packaging

ekd energy chains are supplied in secured device packaging. When removing the packaging and moving the energy chains or parts of them, ensure that the energy chains are free of torsion and tension to avoid mechanical damage.

## Lengthening or shortening

If energy chains are delivered in pieces, proceed with the installation as follows:

Pushing together the links (1) and inserting the flange bolts (5) with a shroud (7) in the chain outside. Then build the radius by inserting the radius bolts (6) (see assembly of detachable bolts). Finally put on the inner shroud (7) and fit the retaining ring (8). A review of the radius by rolling of the energy chain is recommended.

Shortening in the reverse order:

Loosen the retaining rings (8), pull out the flange bolts (5), lifting the shroud (7), pull the radius bolts (6) and remove the links (1).

Energy chains with threaded bolts instead of the retaining rings (8), first unlock the locking plates (18) to solve the locknuts (19). Thereafter, the threaded bolts (17) and pins (6) can be removed and taken from the links (1).




## Implement the connector angle

The connector angles (4) are orientated to the outer radius and to the chain center (normal end mounted). By loosening the retaining rings (8), drag the flange bolts (5), lift off the shroud (7) and pull the radius bolts (6) the connector angles (4) can be disassembled and placed in a different position.


## Bending radius

Loosen the retaining rings (1) and lift off the shrouds (7). Implement the radius bolts (6) according to table (page 89). Then mounting the shrouds (7) and retaining Rings (1).

The plug-in schedule for the different radii can be found engraved on the double connector links (3).








## assembly of radius bolts




**SLE**    **120**    **220**    **320**    **520**    **620**

radius	60	100	150	200	250
radius	100	150	200	250	300
radius	150	200	250	300	400
radius	250	250	300	400	500
radius	-	300	400	500	600




## Stay removal



The stays (9) are fastened with serrated screws (10) to the links (1). They can be removed by unscrewing the four screws (10).

Stay lengths up to 600 mm are available with quick assembly.




## Quick assembly

In quick assembly only two screws must be tightened or loosened. The stays (9) are moved with the groove on the rivet and the serrated screw (10) snapped in the recess and tightened.



## Cover Silver Star

The covers of the closed version can be removed like the stays by loosening the four serrated screws (10). The spacers (13) remain on the links.



## Stainless steel bands

To protect the lines against external damage and pollution the chains can be equipped with steel or stainless steel bands in the inner and outer radius. The edges of the steel bands are circular smoothed to avoid injury. Stainless steel and steel bands are fastened with band holders screwed on sides and with screwed connections on each end of the chain.

## Final assembly



The installation height should not fall below the level  $H = (50 \text{ plus two times bend radius plus link height})$ .  
The pretension of cable carrier is taken into account with the additional space of 50 mm.

First is the fixed connection (F) and then mount the movable connection with the specified bolt size (see SLE connectors).  
Compliance with the maximum free carrying length is of vital importance for the life time of the energy chain, both during the installation as well as during operation. An overload of the energy chain can lead to damage and premature wear.

If the energy chain is provided with support elements, the assembly of these must take place before the installation of the chain in order to avoid even a short-term stress point.

An energy chain may never exceed the free carrying length without support rollers.

The height of the moved connector must be adjusted so that the connector link is moving with a maximum of 5 mm distance from the base of the supporting roller.



## Maintenance of the energy chain

PLE energy chains are maintenance free. Like every mechanical system this will depend on the ambient conditions so wear will occur which must be observed.

In case of the energy chain has to be exchanged.

For long travels or in a circular motion, the energy chains are often equipped with sliding elements. These allow sliding of the upper part of the chain on a suitable surface (eg, slider-slider, slider-steel, glide bar).

The sliders wear depends on the application. The slider surfaces should be checked at regular intervals. With a thickness of 1-2 mm sliders have to be replaced.

**SLE parts 87** 1

SLE link	material	standard (galvanized) hardened (carbured) stainless steel
----------	----------	---

4

2

connector link single

3

connector link double

**R 60, 100, 150, 250**

SLE link	galvanized	carbur.	stainl.steel
120	0110	-	1738
121	0110	-	1738
128	0110	-	1738

connector link single	galvanized	carbur.	stainl. steel	connector link double	galvanized	carbur.	stainl. steel
104	104	-	-	105	105	-	-
104	104	-	-	105	105	-	-
104	104	-	-	105	105	-	-

**R 100, 150, 200, 250, 300**

SLE link	galvanized	carbur.	stainl.steel
220	0117	0821	1739
221	0117	0821	1739
225	0117	0821	1739
228	0117	0821	1739

**R 100, 150, 200, 250, 300**

connector link single	galvanized	carbur.	stainl. steel	connector link double	galvanized	carbur.	stainl. steel
115	115	-	-	116	116	-	-
115	115	-	-	116	116	-	-
115	115	-	-	116	116	-	-
115	115	-	-	116	116	-	-

**R 150, 200, 250, 300, 400**

SLE link	galvanized	carbur.	stainl.steel
320	0147	1725	1726
321	0147	1725	1726
325	0147	1725	1726
328	0147	1725	1726

**R 150, 200, 250, 300, 400**

connector link single	galvanized	carbur.	stainl. steel	connector link double	galvanized	carbur.	stainl. steel
145	145	-	-	146	146	-	-
145	145	-	-	146	146	-	-
145	145	-	-	146	146	-	-
145	145	-	-	146	146	-	-
145	145	-	-	146	146	-	-

**R 200, 250, 300, 400, 500**

SLE link	galvanized	carbur.	stainl.steel
510 / 520	0703/0175	1727	1730
521 / 511	0703/0175	1727	1730
525 / 515	0703/0175	1727	1730
528 / 518	0703/0175	1727	1730

**R 200, 250, 300, 400, 500**

connector link single	galvanized	carbur.	stainl. steel	connector link double	galvanized	carbur.	stainl. steel
173	173	-	-	174	174	-	-
173	173	-	-	174	174	-	-
173	173	-	-	174	174	-	-
173	173	-	-	174	174	-	-
173	173	-	-	174	174	-	-


**R 250, 300, 400, 500, 600**

SLE link	galvanized	carbur.	stainl.steel
620	0878	-	-
621	0878	-	-
625	0878	-	-
628	0878	-	-

**R 250, 300, 400, 500, 600**

connector link single	galvanized	carbur.	stainl. steel	connector link double	galvanized	carbur.	stainl. steel
877	877	-	-	876	876	-	-
877	877	-	-	876	876	-	-
877	877	-	-	876	876	-	-
877	877	-	-	876	876	-	-
877	877	-	-	876	876	-	-

# SLE PART NUMBERS



SLE parts 87

SLE shroud retaining ring radius bolt flange bolt C-profile T-profile ASA / ASI distance filler serrated screw

SLE	St		VA	St	CuSn		St	VA			left		right		
120	0107	-	0109	-	0106	-	0108	-	0692	-	-	-	-	0127	(M4x12)
121	0107	-	0109	-	0106	-	0108	-	0692	-	-	-	-	0127	
128	0107	-	0109	-	0106	-	0108	-	0692	-	-	-	-	0127	
220	0119	0137	0118	0136	0120	0121	0122	0134	0124	0141	-	-	-	0127	(M4x12)
221	0119	0137	0118	0136	0120	0121	0122	0134	0124	0141	-	-	-	0127	
225	0119	0137	0118	0136	0120	0121	0122	0134	0124	0141	1065	1066	1670	1404	0127
228	0119	0137	0118	0136	0120	0121	0122	0134	0124	0141	-	-	-	0127	
320	0149	0166	0148	0167	0150	0151	0152	0165	0154	0171	-	-	-	0157	(M5x14)
321	0149	0166	0148	0167	0150	0151	0152	0165	0154	0171	-	-	-	0157	
325	0149	0166	0148	0167	0150	0151	0152	0165	0154	0171	0847	0846	1293	1671	0157
328	0149	0166	0148	0167	0150	0151	0152	0165	0154	0171	-	-	-	0157	
520	0177	0193	0176	0192	0178	0179	0448	1529	0182	0194	-	-	-	0185	(M6x18)
521	0177	0193	0176	0192	0178	0179	0448	1529	0182	0194	-	-	-	0185	(M6x18)
525	0177	0193	0176	0192	0178	0179	0448	1529	0182	0194	0849	0848	1405	1673	0185
528	0177	0193	0176	0192	0178	0179	0448	1529	0182	0194	-	-	-	0185	
620	0872	0176	0192	-	0874	0180	-	0182	0851	-	-	-	-	0185	(M6x18)
621	0872	0176	0192	-	0874	0180	-	0182	0851	-	-	-	-	0185	
625	0872	0176	0192	-	0874	0180	-	-	-	-	0957	0956	1406	1674	0185
628	0872	0176	0192	-	0874	0180	-	0182	0851	-	-	-	-	0185	



SLE parts 87

11



PZ



PTF PT 55 PT 75



LL 25



LL 50



LS

SLE

120	0691		0112			-	-	-		-	-	1665
121	0691		0112			-	-	-		-	-	1665
128	0691		0112			-	-	-		-	-	1665
220	0778	1519	0779	1658		0879	0879	0880		1663	1664	1665
221	0778	1519	0779	1658		0879	0879	0880		1663	1664	1665
221	0778	1519	0779	1658		0879	0879	0880		1663	1664	1665
225	0778	1519	0779	1658		0879	0879	0880		1663	1664	1665
228	0778	1519	0779	1658		0879	0879	0880		1663	1664	1665
320	0163	1678	1659	1660		0879	0879	0880		1663	1664	1665
321	0163	1678	1659	1660		0879	0879	0880		1663	1664	1665
325	0163	1678	1659	1660		0879	0879	0880		1663	1664	1665
328	0163	1678	1659	1660		0879	0879	0880		1663	1664	1665
520	0719	1679	1661	1662	1680	0879	0879	0880		1663	1664	1665
521	0719	1679	1661	1662	1680	0879	0879	0880		1663	1664	1665
525	0719	1679	1661	1662	1680	0879	0879	0880		1663	1664	1665
528	0719	1679	1661	1662	1680	0879	0879	0880		1663	1664	1665
620	1257	1110	-	-		-	-	-		-	-	-
621	1257	1110	-	-		-	-	-		-	-	-
625	1257	1110	-	-		-	-	-		-	-	-
628	1257	1110	-	-		-	-	-		-	-	-

# SLE PART NUMBERS

## plastic inserts

diameter in mm

SLE 10 15 20 25 30 35 40 45 50 55 60 65 70

120	-	-	-	-	-	-	-	-	-	-	-	-	-
121	-	-	-	-	-	-	-	-	-	-	-	-	-
128	-	-	-	-	-	-	-	-	-	-	-	-	-



220	649	650	651	652	653	-	-	-	-	-	-	-	-
221	649	650	651	652	653	-	-	-	-	-	-	-	-
225	649	650	651	652	653	-	-	-	-	-	-	-	-
228	649	650	651	652	653	-	-	-	-	-	-	-	-




















320	654	665	656	657	658	659	660	661	662	-	-	-	-
321	654	665	656	657	658	659	660	661	662	-	-	-	-
325	654	665	656	657	658	659	660	661	662	-	-	-	-
328	654	665	656	657	658	659	660	661	662	-	-	-	-



520	1628	663	664	665	666	667	668	669	670	671	672	714	715
521	1628	663	664	665	666	667	668	669	670	671	672	714	715
525	1628	663	664	665	666	667	668	669	670	671	672	714	715
528	1628	663	664	665	666	667	668	669	670	671	672	714	715

620	-	-	-	-	-	-	-	-	-	-	-	-	-
621	-	-	-	-	-	-	-	-	-	-	-	-	-
625	-	-	-	-	-	-	-	-	-	-	-	-	-
628	-	-	-	-	-	-	-	-	-	-	-	-	-

SLE	plastic- insert profile	aluminium insert profile	foam	sliders
120	-	-	-	
121	-	-	-	
128	-	-	-	1443  1762 from R200
220	0 827	1649	0730	
221	0 827	1649	0730	
225	0 827	1649	0730	
228	0 827	1649	0730	1444 
				
320	1646	1650	0731	
321	1646	1650	0731	
325	1646	1650	0731	
328	1646	1650	0731	1445  1448 
				
520	1647	1651	0732	
521	1647	1651	0732	
525	1647	1651	0732	
528	1647	1651	0732	1446 
				
620	1648	1652	-	
621	1648	1652	-	
625	1648	1652	-	
628	1648	1652	-	1447 
				

# SLE PART NUMBERS



SLE damping element

screw nut

glide disc

St vz VA

D45

120				0694		0693 0969 (compl.)			
121				0694		0693 0969 (compl.)			
128				0694		0693 0969 (compl.)			

D55

D70

220	0819	0826	0825	0123	0138	0128 0963 (compl.)	0129 0964 (compl.)		
221	0819	0826	0825	0123	0138	0128 0963 (compl.)	0129 0964 (compl.)		
225	0819	0826	0825	0123	0138	0128 0963 (compl.)	0129 0964 (compl.)		
228	0819	0826	0825	0123	0138	0128 0963 (compl.)	0129 0964 (compl.)		

D80

D95

320	0819	0826	0825	0153	1718	0158 0965 (compl.)	0159 0966 (compl.)		
321	0819	0826	0825	0153	1718	0158 0965 (compl.)	0159 0966 (compl.)		
325	0819	0826	0825	0153	1718	0158 0965 (compl.)	0159 0966 (compl.)		
328	0819	0826	0825	0153	1718	0158 0965 (compl.)	0159 0966 (compl.)		

D105

D120

D155

D170

520	0819			0181		0186 0967 (compl.)	0187 0968 1575 (br. )	1538	1539
521	0819			0181		0186 0967 (compl.)	0187 0968 1575 (br. )	1538	1539
525	0819			0181		0186 0967 (compl.)	0187 0968 1575 (br. )	1538	1539
528	0819			0181		0186 0967 (compl.)	0187 0968 1575 (br. )	1538	1539


620

621

625

628

## Support brackets and support rollers



Support rollers are used when half of the travel exceeds the free carrying length ( $L_v > 2LF$ ). Support rollers allow an four times extension of travel distance (see design guidelines). The order of support rollers SR with support brackets for SLE ( $\varnothing 100$  for all sizes) contains the following information:

### SR width of support [cm] / $\varnothing 100$ x height of bracket

The width of the support (A) depends on the width of the steel chain (see table). The height (H) of the support depends on the bending radius of the used steel chain:  $H = 2R + \text{max. } 5\text{mm}$

For example, bend radius 200 mm, stay length 215 mm:

### SR 25 / $\varnothing 100$ x 400

The steel support rollers are delivered with robust and high-quality support frames, which have been in extreme applications. The height of the moved connector must be adjusted with a maximum 5mm distance from the base of the supporting roll. As an alternative to steel rollers SR, plastic support rollers PR for plastic chains are available.

PR	A	B	C	D	E
6	60	126	40	100	92
10	100	166	80	140	132
15	150	216	130	190	115
20	200	266	180	240	165
25	250	316	230	290	215
30	300	366	280	340	365
35	350	416	330	390	315
40	400	466	380	440	365
45	450	516	430	490	415
50	500	566	480	540	465
55	550	616	530	590	515
60	600	666	580	640	565
65	650	716	630	690	615
70	700	766	680	740	665
75	750	816	730	790	715
80	800	866	780	840	832
85	850	916	830	890	882
90	900	966	880	940	932
95	950	1016	930	990	982
100	1000	1066	980	1040	1032

SR	A	B	C	D	max. stay length
10	100	166	80	140	65
15	150	216	130	190	115
20	200	266	180	240	165
25	250	316	230	290	215
30	300	366	280	340	365
35	350	416	330	390	315
40	400	466	380	440	365
45	450	516	430	490	415
50	500	566	480	540	465
55	550	616	530	590	515
60	600	666	580	640	565
65	650	716	630	690	615
70	700	766	680	740	665
75	750	816	730	790	715

## Flange rollers

The flange rollers are used for very long chains in combination with a support railing with supporting rollers and support frames (see design guidelines).

## Guide rollers for steel chains

Guide rollers are used for steel chains in arrangement u (moving end downside, see arrangements). In this case provide a trough or a corresponding support rail.

	v
SL 220	44
SL 320	46
SL 520	50
SL 620	50

## Gliding discs for steel chains

For the SLE in arrangement w (lying horizontally on the side) for the longest travel distance or in arrangement k (circular) gliding discs are used. The gliding discs are made of high quality, highly abrasion-resistant materials. In both arrangements a guide is necessary.

## Shelf troughs for steel chains

Shelf troughs consist of two standard angular channels that are welded together from 3m lengths. Shelf troughs will be used if a smooth and precise guidance of steel chains is necessary.

**Important for the assembly:** Weld angular channels smooth and without any offset and clean the weld seams. In the entire shelf area no projections or disturbing contours may be present (eg, screw heads, nuts,).

## Support carriage for steel chains

Steel chains with support carriage are used for long travel distances and very high additional weights in a counter-chain arrangement. With side-mounted guide rollers the energy chains are supported on the support carriage.

**Technical Features:** No push - just pull-tension, large travel distances, extreme additional loads, smooth running, long life.

